



PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9 NOT CONNECTED
10	10
11	11
12	12
13	13
14	14
15	15
SHELL	SHELL (DRAIN WIRE)

ITEM NO	LENGTH(mm)
11.01.6618	1800+100/-0
11.01.6630	3000+100/-0

NOTE:

1. Electrical test:
(1).100% open short & miss wire test;
2. RoHS and Reach COMPLIANT
3. CABLE MARKING: COMPUTER INTERFACE CABLE 300V 80°C
4. 1PCS/Roline polybag+label

MATERIAL LIST:

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT' Y	REMARK
⑤	HOOD MOLDED	PVC COLOUR BEIGE	2	
④	SCREW	THUMB SCREW TO BE MOLDED PVC BEIGE , PLATED NICKEL	4	
③	CONNECTOR	HDB 15PIN MALE:SOLDER TYPE, BLUE PBT INSULATION, GOLD FLASH CONTACTS, NICKEL PLATED SHELL	1	
②	CONNECTOR	HDB 15PIN MALE:SOLDER TYPE, BLUE PBT INSULATION, GOLD FLASH CONTACTS, NICKEL PLATED SHELL	1	
①	CABLE	30AWG (30AWG COPPER)*14C+E (30AWG COPPER) +AL-FOIL, JACKET PVC COLOUR: BEIGE OD:φ4.8±0.2MM	1	

ITEM NO.	11.01.6618	11.01.6630
DESC.	ROLINE MONITOR CABLE HD 15M/M Beige Color,PVC,3.0m,Molded	
DESC.	ROLINE MONITOR CABLE HD 15M/M Beige Color,PVC,1.8m,Molded	

		NEW	2012.04.16	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

SECOMP