



1. PLASTIC FIBER CORB (PMMA):OD=0.98mm
2. CLAD (FLUORD POL YMER) :OD=1.0mm
3. PRIMARY JACKET PE,OD=2.2 mm (BLACK)
4. OUTER JACKET PVC, BLACK IN COLOR, OD=4.0 mm

Chart A

**NOTES:**

1. Marking: Bewired Toslink Plastic Fiber 4.0mm PVC Black
  2. CABLE: 4.0mm PLASTIC OPTICAL FIBER CABLE
  3. CONNECTORS: TOSLINK TO TOSLINK
  4. PACKING: 1PC PER PE BAG+ 1PC TAG
  5. PERFORMANCE:
    - $L \leq 2M$ : ATTENUATION SHOULD BE 2.0dB OR LESS
    - $L > 2M$ : ADD 0.2dB/M
- (TEST BY 650±30nm LED LIGHT SOURCE / POWER METER)

1	4.0mm PLASTIC OPTICAL FIBER CABLE	L	M
NO	DESCRIPTION	Q'TY	UNIT

REV.	DESCRIPTION	DATE										
<table border="1"> <tr> <th>REV.</th> <th>TOLERANCE</th> </tr> <tr> <td>.X</td> <td>INCHES M/M</td> </tr> <tr> <td>.XX</td> <td>.015 .30</td> </tr> <tr> <td>.XXX</td> <td>.010 .10</td> </tr> <tr> <td></td> <td>.005 .05</td> </tr> </table>	REV.	TOLERANCE	.X	INCHES M/M	.XX	.015 .30	.XXX	.010 .10		.005 .05	<b>SECOMP</b> TITLE: VALUE Toslink Cable M-M, 5.0m	
REV.	TOLERANCE											
.X	INCHES M/M											
.XX	.015 .30											
.XXX	.010 .10											
	.005 .05											
DRAWN BY	P/N :											
CHECK BY	SCALE	NONE										
APPD BY	UNIT	MM										
	DATE	2012.07.06										
	DRAWING NO.:	B11-CC001402										
	REV.	A										
		1/1										