

# PRODUCT DATASHEET

## ST8SP-EM 19.1 W/865 1500 mm EM

SubstiTUBE STAR PC | Economic LED tubes for electromagnetic control gears



---

### AREAS OF APPLICATION

- Corridors, stairways, parking garages
- Cooling and storage rooms
- Warehouses
- Domestic applications
- General illumination within ambient temperatures from -20...+45 °C

---

### PRODUCT BENEFITS

- Extremely break resistant thanks to cover made of polycarbonate
- High color homogeneity
- Energy savings of up to 68 % compared to conventional 1,500 mm T8 fluorescent lamp
- Instant flickerfree starting

---

### PRODUCT FEATURES

- T8 LED tube with G13 base
- Mercury-free and RoHS compliant
- Luminous efficacy: up to 105 lm/W
- Type of protection: IP20



**TECHNICAL DATA**

Electrical data

Nominal wattage	19.10 W
Rated wattage	19.10 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Nominal current	0.088 A
Type of current	AC
Power factor $\lambda$	> 0.90

Photometrical data

Light color (designation)	Cool Daylight
Rated color temperature	6500 K
Nominal luminous flux	2000 lm
Rated luminous flux	2000 lm
Color rendering index Ra	>80
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	$\leq 6$ sdc

Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s
Rated beam angle (half peak value)	160.00 °

Dimensions & weight



Length with base excl. base pins/connection	1500.00 mm
Tube diameter	27.2 mm
Product weight	165.00 g
Overall length	1513 mm

## Temperatures &amp; operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

## Lifespan

Lifespan	30000 h
Nominal lamp life time	30000 h
Rated lamp life time	30000 h
Number of switching cycles	200000

## Additional product data

Base (standard designation)	G13
Mercury-free	Yes

## Capabilities

Dimmable	No
----------	----

## Certificates &amp; standards

Type of protection	IP20
Standards	CE/CB
Energy efficiency class	A+
Energy consumption	20 kWh/1000h

## Country specific categorizations

ILCOS	DR-19.1/865-G13-27.2/1500
Order reference	ST8SP-1.5M 19,1

## Logistical data

Temperature range at storage	-20...80 °C
------------------------------	-------------

## EQUIPMENT / ACCESSORIES

- Suitable for operation on magnetic control gear

## SAFETY ADVICE

Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

## LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
--------------	---------------------	---------------------------------	---	--------	--------------

---

4058075820333	ST8SP-EM 19.1 W/865 1500 mm EM	Shipping carton box 8	1629 mm x 148 mm x 88 mm	21.22 dm <sup>3</sup>	2430.00 g
---------------	-----------------------------------	--------------------------	-----------------------------	-----------------------	-----------

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### LEGAL ADVICE

When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.