



IB9365-HT-A

Bullet Network Camera

2MP 60fps • Smart Stream III • SNV • WDR Pro • 50M/100M IR • Smart IR II • Smart VCA

- 60 fps @ 1920x1080
- 12 ~ 40mm Motorized lens
- H.265 Compression Technology
- Smart Stream III to Optimize Bandwidth Efficiency
- SNV (Supreme Night Visibility) for Low Light Conditions
- WDR Pro to Provide Extreme Visibility in Extremely Bright or Dark Environments
- Built-in IR illuminators, effective up to 50/100 meters
- Smart IR II Technology to Avoid Overexposure
- Smart Motion Detection to Reduce False Alarms
- Smart VCA (Intrusion Detection, Loitering Detection, Line Crossing Detection)
- Trend Micro IoT Security
- Weather-proof IP66, IP67 and Vandal-proof IK10-rated Housing



Technical Specifications

System Information

Model	IB9365-HT-A (4-9 mm) IB9365-HT-A (12-40 mm)
CPU	Multimedia SoC (System-on-Chip)
Flash	256MB
RAM	1G

Camera Features

Image Sensor	1/2" Progressive CMOS
Max. Resolution	1920x1080 (2MP)
Lens Type	Motorized, Vari-focal, Remote Focus
Focal Length	IB9365-HT-A (4-9 mm): $f = 4 \sim 9$ mm ($f = 3.5 \sim 11.4$ mm, equivalent focal length @ 1/2.8") IB9365-HT-A (12-40 mm): $f = 12 \sim 40$ mm
Aperture	IB9365-HT-A (4-9 mm): F1.3 ~ 2.2 IB9365-HT-A (12-40 mm): F1.8
Auto-iris	P-iris
Field of View	IB9365-HT-A (4-9 mm): 46° ~ 100° (Horizontal) 26° ~ 52° (Vertical) 53° ~ 120° (Diagonal) IB9365-HT-A (12-40 mm): 12° ~ 35° (Horizontal) 7° ~ 19° (Vertical) 14° ~ 40° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut Filter	Yes
IR Illuminators	IB9365-HT-A (4-9 mm): Built-in IR illuminators, effective up to 50 meters with Smart IR II, IR LED*6 IB9365-HT-A (12-40 mm): Built-in IR illuminators, effective up to 100 meters with Smart IR II, IR LED*4
Minimum Illumination	IB9365-HT-A (4-9 mm): 0.015 Lux @ F1.3 (Color) <0.005 Lux @ F1.3 (B/W) 0 Lux with IR illumination on IB9365-HT-A (12-40 mm): 0.075 Lux @ F1.8 (Color) <0.005 Lux @ F1.8 (B/W) 0 Lux with IR illumination on
Tilt Range	90°
Rotation Range	180°
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in)
On-board Storage	Slot type: MicroSD/SDHC/SDXC card slot Seamless Recording

Video

Video Compression	H.265, H.264, MJPEG
Maximum Frame Rate	60 fps @ 1920x1080
Maximum Streams	3 simultaneous streams
S/N Ratio	68 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and bit rate control, Smart Stream III
Image Settings	Time stamp, text overlay, flip and mirror, configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks, scheduled profile settings, HLC, defog, 3DNR, video rotation, EIS

Audio

Audio Capability	Two-way Audio (full duplex)
------------------	-----------------------------

Audio Compression	G.711, G.726
Audio Interface	External microphone input External line output
Network	
Users	Live viewing for up to 10 clients
Protocols	802.1X, ARP, CIFS/SMB, CoS, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS, UDP, UPnP
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Supported, specification available at www.onvif.org
Solution Integration	
Smart Motion Detection	Five-window video motion detection, people detection, time filter
Smart VCA	Intrusion detection, loitering detection, line crossing detection, unattended object detection, missing object detection, face detection *Please access http://license.vivotek.com/ to get the free trial license.
VADP Package	Deep Learning VCA (Smart Motion Detection, Smart VCA), Stratocast, Trend Micro IoT Security
Alarm and Event	
Alarm Triggers	Motion detection, digital input, manual trigger, periodical trigger, system boot, recording notification, camera tampering detection, audio detection, SD card life expectancy, shock detection, cybersecurity events (brute force attack event, cyberattack event, quarantine event)
Alarm Events	Event notification via audio clip, digital output, email, HTTP, FTP, NAS server, SD card File upload via email, HTTP, FTP, NAS server, SD card
General	
Connectors	RJ-45 cable connector for 10/100Mbps Network/PoE connection Audio input Audio output AC 24V power input DC 12V power input Digital input *2 Digital output *2 BNC out
LED Indicator	System power and status indicator
Power Input	AC 24V, DC 12V, IEEE 802.3af PoE Class 0 (Power Redundancy)
Power Consumption	PoE: Max. 12.95/7.86 W (IR on/off) DC 12V: Max. 10.8/5.8 W (IR on/off) AC 24V: Max. 12.5/7.5 W (IR on/off)
Dimensions	IB9365-HT-A (4-9 mm): Ø 121 x 121 x 352.1 mm (w/ junction box) Ø 121 x 121 x 288.1 mm (w/o junction box) IB9365-HT-A (12-40mm): Ø 121 x 121 x 368.9 mm (w/ junction box) Ø 121 x 121 x 305.9 mm (w/o junction box)
Weight	1,254 g
Casing	IP66, IP67, IK10 (Metal Housing)
Safety Certifications	CE, LVD, FCC Class A, VCCI, C-Tick, UL, EN50121-4, BIS
Operating Temperature	Starting Temperature: -10°C ~ 50°C (14°F ~ 122°F) Working Temperature(IR on): -30°C ~ 50°C (-22°F ~ 122°F) Working Temperature (IR off): -30°C ~ 60°C (-22°F ~ 140°F)
Humidity	98%
Warranty	36 months
System Requirements	
Operating System	Microsoft Windows 8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above Internet Explorer 11
Other Players	VLC: 1.1.11 or above
Included Accessories	


Others

Quick installation guide, warranty card, screw pack, alignment sticker, desiccant bag, waterproof accessory bag, junction box, sunshield


Dimensions

IB9365-HT/EHT-A(4-9mm)

w/ junction box




w/o junction box




IB9365-HT-A(12-40mm)

w/ junction box



w/o junction box



Compatible Accessories

Mounting Kits



AM-719
Outdoor Junction Box (Standard Package)

Mounting Kits



AM-312
Pole Mount Adapter

Mounting Kits



AM-412
Corner Mount Adapter