



**WIRE ADDRESS**

P1	P2	P1	P2
1	1	14	14
2	2	15	15
3	3	16	16
4	4	17	17
5	5	18	18
6	6	19	19
7	7	20	20
8	8	21	21
9	9	22	22
10	10	23	23
11	11	24	24
12	12	25	25
13	13	Shell	Shell

- Electrical Test:
- 1.100% TEST OPEN SHORT MIS-WIRE.
  - 2.CONTACT RESISTANCE:3Ω MAX.
  - 3.INSULATION RESISTANCE:5MΩ MIN.
  - 4.HI-POT:300V DC/10MS.

D	45P PVC BEIGE		6	ROLINE RS-232 Cable, DB25 M - M, 3.0m	
C	Screw:#4-40UNC(Nickel Plated,Beige)		4	Item	11.01.3530
B	DB 25P MALE(Blue Insulator, Nickel Plated)		2	Draw	<i>Shake</i> Date: 2020.05.13
A	NON-UL 30AWG*25C + AD.OD=7.0mm BEIGE PVC JACKET.		1	Approval	
PRODUCT SPECIFICATIONS			Quantity	Duty	F16
NUMBER			Unit	Sample NO.	BOM:NO:13887
				Drawings of 1 (2)	Proportion: 1:1
				Unit(mm)	

