



Electrical Test:

- 1.100% TEST OPEN SHORT MIS-WIRE.
- 2.CONTACT RESISTANCE:15Ω MAX.
- 3.INSULATION RESISTANCE:5MΩ MIN.
- 4.HI-POT:300V DC/10MS.
- 5.Real Test Passed 2560*1600P 60HZ
- 6.Real Test Not Twinking,Double Vision and Decolor.

G	45P BLACK PVC	G
F	DVI SHELL(30P BLACK PVC)	PCS
E	DVI SPTE	PCS
D	FERRITE(17.5*10.5*28.5mm)BLACK	PCS
C	Screw : #4-40UNC(Nickel Plated,BLACK MOLDING)	PCS
B	DVI24+1 MALE (Black Insulator,Nickel Plated)	PCS
A	UL20276[28#*1P(CS)+DAMI*7C+28#*1P(BG)+28#*2C(BG)+26#*1C(BG)+ADB,OD=8.5, BLACK PVC JACKET	PCS
F	PRODUCT SPECIFICATIONS	Quantity Unit
NUMBER	1	2
1	2	4
Sample NO.	F16	BOM.NO: 13870
Drawings of 1-(2) Proportion: 1:1 Unit(mm)	A4	SECOMP



ROUTINE Monitor Cable, DVI M - DVI M, (24+1) dual link, 7.5m

Item 11.04.5556

Draw *Make* Date: 2020.03.09

Approval

Duty F16 BOM.NO: 13870