



**Electrical Test:**

1. 100% test on computer, and pass the test on new version of MAC Notebook (USB Bi-Directional testing), solution up to 3840\*2160 @60Hz
2. Use 5V adapter for testing

I	45P PVC Black		G
H	Type C Shell (Black ABS)	1	PCS
G	HDMI Shell (Black ABS)	1	PCS
F	PCBA (IC: PS176+CYPD2119)	1	PCS
E	USB A Male (Black Insulator, Gold Plated)	1	PCS
D	Type C Male (Black Insulator, Gold Plated)	1	PCS
C	HDMI 19P Male (Black Insulator, Gold Plated)	1	PCS
B	Non-UL, 30AWG*1P+24AWG*2C, OD: 3.0mm, Black PVC Jacket	1	PCS
A	UL2725 (32AWG*1P+EAM)*4C+32AWG*1P+32AWG*5C+22AWG*1C+AEB OD: 4.5mm, Black PVC Jacket	1	PCS
Number	Z-11.04.5956	Specification	Q'ty Unit

ROLINE USB Type C to HDMI+USB A Cable, M/M, 2m, black			
Item	11.04.5956		
Draw	<i>Nobe</i>	Date: 2019.03.11	
Approval			
Duty	F16	BOM.NO	
Sample NO.			Drawings of 1 (1) Proportion: 1:1 Unit(mm)   A4

