



PIN OUT

P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
SHELL	SHELL

NOTE:

1. Electrical test:

- (1). 100% open short & miss wire test;
- (2). Insulation resistance: 10Mohm MIN;
- (3). Contactor resistance: 3ohm Max;
- (4). Dielectric strength: 300V DC Min
- 2. Current Rate: 900 mA
- 3. Voltage: 5V DC
- 4. Data Transfer: 5Gbps
- 5. Storage temperature: -20°C~+60°C
- 6. Operation temperature: 0°C~+50°C
- 7. RoHS (EU 2015/863) and REACH Compliant

MATERIAL LIST:

③	OVER MOLDING	PVC Color For black	1	
②	INNER MOLDING	TRANSPAENT LD-PE	2	
①	USB CONNECTOR	USB AF Solder Type, Blue insulation The Pin Gold Plating, the shell for Nickel Plating	2	
NO.	PARTS. NAME	SPECIFICATION STANDARD	QT' Y	REMARK
		NEW	2019-03-20	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

Item No. :	12.99.2997
Colour	Black
DESC.	VALUE USB 3.0 Adapter, A-A, F/F

**SECOMP**