CE100



MINI USB KVM Extender


The CE100 USB KVM Extender with superior video quality and built-in ESD protection allows access to a computer system from a remote USB console (USB keyboard, USB mouse, and monitor).

The CE100 improves on previous designs by: 1) incorporating a compensation adjustment function at the Remote unit for greater video quality; and 2) using inexpensive Cat 5e cable, instead of bulky, expensive, standard cables, to provide a neater, more convenient, more reliable data transfer connection.





Setup --



Features -----

- Extends local PC VGA/keyboard/Mouse to Remote side
- Uses Cat 5e cable to connect the local and remote units
- Easily add or remove computers connected to the installation
- Supports real time DDC communication
- Superior video quality up to 1920 x 1200
- Allow access to a computer from the remote console up to 100 m distance
- Support manual compensation adjustment for better video quality
- No external power supply needed for local unit
- Built-in 8KV/15KV ESD protection (Contact voltage 8KV; Air voltage 15KV)
- Rack mountable

Specifications -----

Function		CE100L	CE100R
	Keyboard	N/A	1 x USB Type A
	-		Female (White) 1 x HDB-15
	Video	N/A	Female (Blue)
1 0113	Mouse	N/A	1 x USB Type A
			Female (White)
KVM Ports	Keyboard	1 x USB Type B	N/A
	/ Mouse	Female (White)	
	Video	_	N/A
		1 x DC Jack	
Unit to Unit		1 x RJ-45 Female (Black)	
Switch		N/A	1 x Knob
Link		1 (Blue)	
LEDs Power		1 (Green)	
Video		1920 x 1200 @ 60 Hz (30m);	
		1280 x 1024 @ 60 Hz (100m)	
Power Consumption		DC5V, 0.5W	DC5V, 1.25W
Operating Temp.		0-50°C	
Storage Temp		-20–60°C	
Humidity		0–80% RH, Non-condensing	
Housing		Metal	
Weight		0.16 kg	
Dimensions (L x W x H)		9.00 x 5.50 x 2.40 cm	
	Console Ports KVM Ports Power Unit to Unit t	Console Ports Keyboard Video Mouse KVM / Mouse Video Power Unit to Unit Link Power Inption Operating Temp. Storage Temp Humidity Housing Weight Dimensions	Console Ports Keyboard N/A KVM Ports Mouse N/A KVM Ports Keyboard / Mouse 1 x USB Type B Female (White) Video 1 x HDB-15 Male (Blue) Power 1 x DO Unit to Unit 1 x RJ-45 Female (White) N/A N/A Link 1 (Gine) Power 1 (Gine) 1280 x 1024 @inption DC5V, 0.5W Operating Temp 0-5 Storage Temp -20- Humidity 0-80% RH, Nichland Housing Memory Me

^{*} Product specifications and appearance are subject to change without notice.

