



2-Port True 4K HDMI Splitter

VS4812

**Stunning True 4K Visuals –
Stable, Reliable Dual-Display Output**




The VS4812 distributes a single HDMI source to two displays simultaneously, delivering stunning True 4K visuals. It features EDID Sync™ for flawless audiovisual synchronization and HDCP 2.2 compliance to guarantee reliable visual performance. Supporting HDR10+, 3D formats, and Deep Color, it offers richer contrast and a wider color spectrum for truly immersive viewing. Its aesthetic, compact, and user-friendly design makes it ideal for home entertainment setups, dual-monitor workstations, and professional AV environments.



Accent Light



Compact Design



18Gbps Max. Bandwidth

Features

EDID Sync™ Smart Display Optimization

Automatically optimizes resolutions and prevents display issues for flawless display presentation

True 4K Dual-Display Sharing

Shares one HDMI source across two True 4K displays for double the visual impact with uncompromised quality

HDMI 3D/Deep Color, HDR10+, HDCP 2.2 Compatible

Guarantees stable performance, broad compatibility, and superior image quality

Master-Class Audio Immersion

Full support for LPCM 7.1, Dolby® Digital & DTS-HD Master Audio™ delivers theatrical-quality surround sound


Pushbutton Output Control

Instantly enables or disables HDMI out 2 with a press of the pushbutton for intuitive, hands-on display management

Aesthetic Compact Form

Slim profile and stylish accent lighting allow integration into any space, perfectly complementing your setting



Installation



Specifications

Video Input	
Interfaces	1 x HDMI Type-A Female (Black)
Impedance	100 Ω
Max. Distance	3 m at 3840 x 2160 @ 60Hz (4:4:4)
Video Output	
Interfaces	2 x HDMI Type-A Female (Black)
Impedance	100 Ω
Max. Distance	3 m at 3840 x 2160 @ 60Hz (4:4:4)
Video	
Max. Data Rate	18 Gbps (6 Gbps per lane)
Max. Pixel Clock	600 MHz
Compliance	HDMI (3D, Deep Color, 4K); HDCP 2.2 Compatible
Max. Resolution	3840 x 2160 @ 60Hz (4:4:4)
Audio	
Input	1 x HDMI Type-A Female (Black)
Output	2 x HDMI Type-A Female (Black)
Connectors	
Power	1 x USB-C (5V/1A)
LEDs	
LED Indicator	2 x Port Indicator (Orange)
Power	2 (Orange, Bottom Side)
Cable Length	
USB Cable	1 x USB Type-C to Type-A (1 m)
Environmental	
Operating Temperature	0 – 40 °C
Storage Temperature	-20 – 60 °C
Humidity	0 – 80% RH, Non-Condensing
Physical Properties	
Housing	Plastic
Weight	0.03 kg
Dimensions (L x W x H)	6.10 x 5.65 x 1.52 cm
Carton Lot	
	20 pcs

Package Contents



ATEN International Co., Ltd.
 3F., No.125, Sec. 2, Datung Rd., Sijhih District.,
 New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 | Fax: 886-2-8692-6767
 www.aten.com | E-mail: marketing@aten.com

Released: 01/2026 V2.0

© Copyright 2026 ATEN® International Co. Ltd. ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners. Product information is subject to change without prior notice. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.