



All references to and depictions of compatible products, including those produced by Sony Interactive Entertainment (PlayStation), or Audio-Technica, are for compatibility demonstration purposes only, not intended to suggest any endorsement or sponsorship by or affiliation with those product manufacturers.

## 2-Port 8K HDMI Splitter

VS5812

### Uncompromised 8K Visuals across Dual-Display




The VS5812 shares a single HDMI source with dual displays, delivering breathtaking 8K @ 60Hz and 4K @ 120Hz visuals. It features EDID Sync™ for flawless audiovisual synchronization and HDCP 2.3 compliance for reliable performance. Supporting HDR10+, VRR, ALLM, Deep Color, and various premium audio formats, it provides ultra-realistic imagery with vibrant color and immersive sound. Its aesthetic, compact, and user-friendly design makes it ideal for premium home theaters, high-end gaming setups, and professional AV environments.



Accent Light



Compact Design



48Gbps Max. Bandwidth

## Features

### EDID Sync™ Smart Display Optimization

Automatically optimizes resolutions and prevents display issues for flawless display presentation

### Extreme Dual-Display Resolution Distribution

Shares one HDMI source across two displays, delivering simultaneous 8K @ 60Hz and 4K @ 120Hz visuals

### Variable Refresh Rate (VRR)

Synchronizes frame rate to eliminate screen tearing and stutter for ultra-smooth gameplay

### Auto Low Latency Mode (ALLM)

Automatically switches to game mode, dramatically reducing input lag for responsive control

### HDMI 3D/Deep Color, HDR10+, HDCP 2.3 Compatible

Guarantees stable performance, broad compatibility, and superior image quality

### Master-Class Audio Immersion

Full support for LPCM 7.1, Dolby® Digital & DTS-HD Master Audio™ delivers theatrical-quality surround sound


### Pushbutton Output Control

Instantly enables or disables HDMI out 2 with a press of the pushbutton for intuitive, hands-on display management

### Aesthetic Compact Form

Slim profile and stylish accent lighting allow integration into any space, perfectly complementing your setting



## Installation



## Specifications

Video Input	
Interfaces	1 x HDMI Type-A Female (Black)
Impedance	100 Ω
Max. Distance	1.5 m at 7680 x 4320 @ 60Hz (4:2:0)
Video Output	
Interfaces	2 x HDMI Type-A Female (Black)
Impedance	100 Ω
Max. Distance	1.5 m at 7680 x 4320 @ 60Hz (4:2:0)
Video	
Max. Data Rate	48 Gbps
Compliance	HDMI (3D, Deep Color, 8K) HDCP 2.3 Compatible
Max. Resolution	7680 x 4320 @ 60Hz (4:2:0)
Audio	
Input	1 x HDMI Type-A Female (Black)
Output	2 x HDMI Type-A Female (Black)
Connectors	
Power	1 x USB-C (5V/1A)
Cable Length	
USB Cable	1 x USB Type-C to Type-A (1 m)
LEDs	
LED Indicator	2 x Port Indicator (Orange)
Power	2 (Orange, Bottom Side)
Environmental	
Operating Temperature	0 – 40 °C
Storage Temperature	-20 – 60 °C
Humidity	0 – 80% RH, Non-Condensing
Physical Properties	
Housing	Plastic
Weight	0.03 kg
Dimensions (L x W x H)	6.10 x 5.65 x 1.52 cm
Carton Lot	
	20 pcs

## Package Contents



### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datung Rd., Sijhih District,  
New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 | Fax: 886-2-8692-6767  
www.aten.com | E-mail: marketing@aten.com

Released: 01/2026 V2.0

© Copyright 2026 ATEN® International Co. Ltd. ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners.

Product information is subject to change without prior notice.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.