



Note:  
 ROHS 2.0 & REACH Compliant  
 2. The out jacket is conform to IEC60332-1, EN60754-2, EN 61034-2  
 3. Min. Bending Radius: Static: 30mm, Dynamic: 60mm

Test:  
 Grade Designation: Each to Reference

### MATERIAL LIST:

|   |  |      |
|---|--|------|
| ⑫ | LC Dust Cap White  | 2pcs |
| ⑪ | LC UPC SM Ceramic Ferrule  | 2pcs |
| ⑩ | LC Blue Duplex Clip  | 1pcs |
| ⑨ | LC Duplex Connector Blue   | 2pcs |
| ⑧ | LC 3.0 Boot White  | 2pcs |
| ⑦ | LSH 3.0 Boot Green   | 2pcs |
| ⑥ | Fiber Optical Cable Yellow OS2 G657. A2 9/125um Duplex $\phi$ 3.0*6.0mm LSZH | L    |
| ⑤ | Black Heat Shrink Tube   | 2pcs |
| ④ | Ring 1, 2  | 4pcs |
| ③ | LSH 3.0 Boot Green   | 2pcs |
| ② | LSH Connector Green  | 2pcs |
| ① | LSH Metal Dust Cap   | 2pcs |

| Type            | Single-Mode   |
|-----------------|---|
| Insertion Loss  | $\leq 0.2$ dB   |
| Return Loss     | UPC $\geq 50$ dB, APC $\geq 60$ dB                              |
| Test Wavelength | 1310nm  |
| ITEM NO.        | DESC.   |
| 21.15.9510      | ROLINE FO Jumper Cb1 LSH APC-LC UPC, Duplex, 9/125um, OS2, 0.5m |
| 21.15.9511      | ROLINE FO Jumper Cb1 LSH APC-LC UPC, Duplex, 9/125um, OS2, 1m   |
| 21.15.9512      | ROLINE FO Jumper Cb1 LSH APC-LC UPC, Duplex, 9/125um, OS2, 2m   |
| 21.15.9513      | ROLINE FO Jumper Cb1 LSH APC-LC UPC, Duplex, 9/125um, OS2, 3m   |
| 21.15.9515      | ROLINE FO Jumper Cb1 LSH APC-LC UPC, Duplex, 9/125um, OS2, 5m   |
| 21.15.9516      | ROLINE FO Jumper Cb1 LSH APC-LC UPC, Duplex, 9/125um, OS2, 7.5m |
| 21.15.9517      | ROLINE FO Jumper Cb1 LSH APC-LC UPC, Duplex, 9/125um, OS2, 10m  |

| NO. | SPECIFICATION STANDARD  | QT'Y                          | REMARK    |
|-----|-------------------------|-------------------------------|-----------|
|     | Add Min. Bending Radius | 2022-1-24                     | A1        |
|     | NEW                     | 2018-05-07                    | A         |
| BY  | CHK                     | REVISION RECORD MODIFICATIONS | DATE REV. |

# SECOMP