

## 4MP Fixed-focal 4G Battery Bullet Network Camera

# DH-BF4CA-4G-XL



#### **Series Overview**

Driven by industry-leading technology, Dahua Wireless Series network cameras are highly precise and easy to install, producing high-quality images. They have strong wireless connection capabilities and do not require network cables, eliminating the need for a professional construction team. This series of cost-effective cameras supports local storage and is dustproof and waterproof. It is ideal for small and medium-sized scenes such as retail stores, homes, and other small and medium-sized enterprises.



#### 4MP

Clear images with sharp details



#### AOV (Always-On Video) Mode

24/7 protection with all-day recording and ultra-low power consumption



### **4G Connection**

Expands your connectivity with 4G





#### Long-lasting Power, **Non-stop Protection**

Uninterrupted operations through battery and solar charging



## **Sound and Light Alarm**

Provides instant alarms to deter



### **Supports Micro SD Card**

Low-cost storage



#### **Al Precise Detection with Quick Wake Up**

Accurate human and vehicle detection with instant alerts



## **Smart Dual Light**

Captures color details for post-event



### H.265

Advanced H.265 compression





#### **IP66 Protection**

Withstands harsh environments



## **Upgrade Your Experience with DMSS**

Intuitive AloT app for individual security



## **Remote Management**

Live view and recording history



## **Notifications and Alerts**

Accurate and timely



## **Easy sharing**

Safer device sharing with family and friends



## **High Security**

Stay secure with all data encrypted











## **Specifications**

#### Camera

Image Sensor 1/3" CMOS

Max. Resolution 2560 (H) × 1440 (V)

Up to 15 m (49.21 ft) (IR) Illumination Distance Up to 20 m (65.62 ft) (Warm light)

Illuminator Number 2 (Multi-core (IR + warm) light)

Tilt: -60° to 0° Rotation: 0° to 360°

12 m (the height of device is 2.5 m, placed

PIR Sensor Distance 8 m (the height of the device is 2 m, placed at an angle of 30° from the horizontal)

Fixed-focal Lens Type Focal Length 2.1 mm

Max. Aperture F1.6

Field of View H: 122.5°; V: 66°; D: 144.5°

## **Intelligence**

Angle Adjustment

Human Detection Yes Vehicle Detection Yes

#### **Audio and Video**

Video Compression H 265

Main stream: 2560 × 1440@(1–15 fps)

Video Frame Rate

\*The values above are the max. frame rates of each stream; for multiple streams, the values will be

subjected to the total encoding capacity.

Video Bit Rate H.265: 32 kbps-4096 kbps

Auto(ICR)/Color/B/W Day/Night

WDR

Motion Detection OFF/ON (4 areas, rectangular)

Built-in MIC Yes, built-in Mic Built-in Speaker Yes, built-in speaker

G.711a; G.711Mu; PCM Audio Compression

## What's in the box









Bracket × 1 Pin x 1



Quick Start Guide × 1 Power Cable × 1

Legal and regulation

## **Network**

Carrier Network System

(-EAU): FDD-LTE: B1/B3/B5/B7/B8/B20/B28; Applicable regions: Europe, Middle East, Africa Power class 3: 23dBm ±2.7dB (-LA): FDD-LTE: B2/B3/B4/B5/B7/B8/B28/B66;

Micro SD card (support max. 512 GB)

Applicable regions: Latin America Power class 3: 23dBm ±2.7dB

Management Software DMSS

Mobile Client Android;iOS

### **General**

Storage

CE-LVD: EN62368-1;

CE-EMC: Electromagnetic Compatibility Directive Certifications

CE-RED: Radio Equipment Directive 2014/53/EU

Built in 32Wh lithium battery Power Supply

Charging: USB Type-C

Ultra power saving mode: 0.04 W Power saving mode: 0.041 W

Power Consumption AOV mode: 0.2 W

Performance mode: 1.2 W

Operating Temperature -20 °C to +60 °C (-4 °F to +140 °F)

Operating Humidity ≤95% (RH), non-condensing

Protection IP66

Camera Button Reset Button; Power Button

Casing Material

**Product Dimensions** 186.5 mm × Φ65.0 mm (7.34" × Φ2.56")

Net Weight 0.37 kg (0.82 lb)

## **Battery**

Power:

**Battery Capacity** 32.4 Wh

