

# Filter Fan Air flow 61 m<sup>3</sup>/h, 24V DC, IP54

## CATALOG NUMBER

### EF200-24R5



This vertical filter fan, EF, with a IP 54 protection degree, is easy to install thanks to its click-in feature. Unnecessary downtime is avoided, since water and dust are prevented from entering the enclosure through the filter, and the reliable fan motor will ensure constant ventilation.

## INDUSTRY STANDARDS

cRUus\_UL

CE UKCA

EAC

## FEATURES

Description: Filter fan for forced ventilation. nVent HOFFMAN filter fans save time on installation as they are installed with a click-in system without screws. The hinged front cover can be easily opened for quick and easy filter replacement. The airflow direction and the connection position can easily be changed.

Material: Front cover manufactured from injection-moulded thermoplastic, self-extinguishing, UL94V0.

Temperature range: -40 °C to +55 °C.

Protection: IP 54, TYPE 12.

Pack quantity: One fan with filter.

The filter fan is reliable due to its high quality motor, as well as being easy to install

Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the enclosure and the reliable motor ensures that there is constant ventilation

The click-in feature reduces the customer's labour cost due to the ease of installation

The filter fan should be installed together with at least one exhaust filter, EFA

Bearing Type: Sleeve

## PRODUCT ATTRIBUTES

Airflow Volume, Without Filter: 61/67m<sup>3</sup>/h

Airflow Volume, With Filter: 44/50m<sup>3</sup>/h

Airflow: 61m<sup>3</sup>/h

Height: 145mm

Width: 145mm

Depth: 74mm

Cutout Size: 125 x 125mm

Voltage DC: 24V

Protection Rating: IP54; NEMA Type 12

Material: Thermoplastic

Finish: Smooth

Color: Light Gray

Color Code: RAL 7035

Nominal Current: 0.21A

Connection Type: 310 mm Cable

Noise Level: 44dB(A)

Weight: 0.45kg

## WARNING

---

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

**CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE**