

NETGEAR M4350-24X8F8V Managed L3 10G Ethernet (100/1000/10000) Power over Ethernet (PoE) 1U Schwarz

Marke : NETGEAR

Artikel-Code: XSM4340V-100NES

Produktname : M4350-24X8F8V

NETGEAR M4350-24X8F8V. Switch-Typ: Managed, Switch-Ebene: L3. Basic Switching RJ-45 Ethernet Ports-Typ: 10G Ethernet (100/1000/10000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24. Vollduplex. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 1040 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Power over Ethernet (PoE). Rack-Einbau, Formfaktor: 1U



Management features		Multicast features	
Switch type *	Managed	Multicast Listener Discovery (MLD) snooping	✓
Switch layer	L3		
Quality of Service (QoS) support	✓		
Web-based management	✓		
ARP inspection	✓		
Ports & interfaces		Protocols	
Basic switching RJ-45 Ethernet ports quantity *	24	Management protocols	SNMP V1, V2, V3
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	GARP VLAN Registration Protocol (GVRP)	✓
10G Ethernet (copper) ports quantity	24	Routing protocols	OSPF, OSPFv2, OSPFv3, RIP, RIP-1, RIP-2
SFP+ module slots quantity	8		
SFP28 ports quantity	8	Design	
Network		Rack mounting *	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ak, IEEE 802.3bz, IEEE 802.3u	Stackable *	✓
10G support *	✓	Form factor	1U
Full duplex	✓	Product colour	Black
Policy-based routing	✓	LED indicators	✓
Flow control support	✓	Airflow direction	Front-to-back airflow
Link aggregation	✓	Performance	
Broadcast storm control	✓	Built-in processor	✓
Rate limiting	✓	Processor model	ARM Cortex-A57
Spanning tree protocol	✓	Processor frequency	1800 MHz
6to4 tunnel	✓	Memory type	DDR4-SDRAM
IPv4 routes	512	Internal memory	4096 MB
IPv6 routes	256	Flash memory	512 MB
VLAN support	✓	sFlow	✓
		Power	
		Power source *	AC
		Power supply included *	✓
		Power consumption (typical)	151.8 W
		Power consumption (max)	464 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✓
		Power over Ethernet 4PPoE (PoE++) ports quantity	24

Network		Power over Ethernet (PoE)	
Virtual LAN features	MAC address-based VLAN, Private VLAN, Voice VLAN	Power over Ethernet (PoE) power per port	90 W
Number of VLANs	4093	Total Power over Ethernet (PoE) budget	1770 W
Data transmission		Other features	
Switching capacity *	1040 Gbit/s	Power supply	750 W
Throughput	773.76 Mpps	Operational conditions	
MAC address table *	16000 entries	Operating temperature (T-T)	0 - 45 °C
Store-and-forward	✓	Storage temperature (T-T)	-20 - 70 °C
Latency (10 Gbps)	2.7 µs	Operating relative humidity (H-H)	0 - 90%
Jumbo frames support	✓	Storage relative humidity (H-H)	0 - 95%
Jumbo frames	12000	Operating altitude	0 - 3000 m
Packet buffer memory	64 MB	Non-operating altitude	0 - 3000 m
Security		Weight & dimensions	
DHCP features	DHCP Option 150, DHCP Option 66, DHCP Option 67, DHCP relay, DHCP server, DHCP snooping	Width	440 mm
Access Control List (ACL)	✓	Depth	400 mm
Access Control List (ACL) egress	1023	Height	43.2 mm
Access Control List (ACL) ingress	511	Weight	7.24 kg
IGMP snooping	✓	Packaging content	
IGMP proxy	✓	Cables included	AC, USB Type-C
MAC address filtering	✓	Quick start guide	✓
Static port security	✓	Rack mount kit	✓
Loop protection	✓	Packaging data	
BPDU filtering/protection	✓	Included power plug types	EU, UK, NA
Authentication	Guest VLAN, MAC-based authentication	Sustainability	
Root protection	✓	Sustainability compliance	✓
Password protection	✓	Certificates	
DoS attack prevention	✓	Compliance certificates	BSMI, CCC, CE, Federal Communications Commission (FCC), Low Voltage Directive (LVD)
Authentication type	RADIUS, TACACS+		
Queue scheduling algorithms	Strict Priority Queue (SPQ), Weighted random early detection (WRED)		
Multicast features			
Multicast support	✓		



0606449165135



606449165135

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.