

ZYXEL

Zyxel GS2220-10-EU0101F Netzwerk-Switch Managed L2 Gigabit Ethernet (10/100/1000) Schwarz

Marke : Zyxel

Artikel-Code: GS2220-10-EU0101F

Produktname : GS2220-10-EU0101F

Zyxel GS2220-10-EU0101F. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 10. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 20 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack-Einbau



Management-Funktionen		Multicast-Funktionen	
Switch-Typ *	Managed	Multicast Unterstützung	✓
Switch-Ebene	L2	Design	
Quality of Service (QoS) Support	✓	Rack-Einbau *	✓
Web-basiertes Management	✓	Produktfarbe	Schwarz
Konfiguration der Standorteinstellungen (CLI)	✓	Zertifizierung	LVD, BSMI FCC 15 A, CE EMC A, BSMI ENC RoHS A
Systemereignisprotokoll	✓	Leistungen	
Anschlüsse und Schnittstellen		RAM-Speicher	256 MB
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	10	Flash-Speicher	32 MB
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Upgradefähige Firmware	✓
Netzwerk		Ventilatorlos	✓
Netzstandard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	1213492 h
	10G-Unterstützung *	Leistung	
Kupfer Ethernet Verkabelungstechnologie	10BASE-TX, 1000BASE-T	AC Eingangsspannung	100 - 240 V
Unterstützung Datenflusssteuerung	✓	AC Eingangsfrequenz	50 - 60 Hz
Link Aggregation	✓	Stromverbrauch (max.)	11 W
Broadcast-Sturmkontrolle	✓	Power over Ethernet (PoE)	
Ratenbeschränkung	✓	Power over Ethernet (PoE) *	✗
Spannbaum-Protokoll	✓	Betriebsbedingungen	
VLAN-Unterstützung	✓	Betriebstemperatur	0 - 50 °C
Virtuelle LAN-Funktionen	Port-based VLAN, Private VLAN, Protocol-based VLAN, Voice VLAN	Temperaturbereich bei Lagerung	-40 - 70 °C
Datenübertragung		Relative Luftfeuchtigkeit in Betrieb	10 - 95%
Routing-/Switching-Kapazität *	20 Gbit/s	Luftfeuchtigkeit bei Lagerung	10 - 95%
Transferrate	15 Mpps	Wärmeableitung	37,51 BTU/h
MAC-Adressentabelle *	16000 Eintragungen	Gewicht und Abmessungen	
		Breite	267 mm
		Tiefe	162 mm
		Höhe	44 mm
		Gewicht	1,3 kg

Datenübertragung		Verpackungsdaten	
Datenpaket-Pufferspeicher	1,5 MB	Mitgelieferte Kabel	AC
Sicherheit		Verpackungsbreite	375 mm
DHCP-Funktionen	DHCP client, DHCP relay, DHCP snooping, DHCPv6 client, DHCPv6 relay	Verpackungstiefe	235 mm
Zugriffskontrollliste	✓	Verpackungshöhe	61 mm
IGMP snooping	✓	Paketgewicht	2,21 kg
Unterstützte Sicherheitsalgorithmen	SNMP, SNMPv2, SNMPv3, SSH-2, SSL/TLS	Logistikdaten	
MAC Adressen Filtern	✓	Warentarifnummer (HS)	85176990
Authentifizierung	Gast VLAN, MAC-basierte Authentifizierung		
Authentifizierungstyp	IEEE 802.1x, RADIUS		



4718937607365

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAY-2023. Prints or copies of Information are only valid on the printed Publication date