

Zyxel XS1930-12F-ZZ0101F Netzwerk-Switch Managed L2/L3 Schwarz



Marke : Zyxel

Artikel-Code: XS1930-12F-ZZ0101F

Produktname : XS1930-12F-ZZ0101F

Zyxel XS1930-12F-ZZ0101F. Switch-Typ: Managed, Switch-Ebene: L2/L3. MAC-Adressentabelle: 16000 Eintragungen, Routing-/Switching-Kapazität: 240 Gbit/s. Netzstandard: IEEE 802.1p, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3z. Netzstecker: AC-Eingangsbuchse. Rack-Einbau

Management-Funktionen		Sicherheit	
Switch-Typ *	Managed	IGMP snooping	✓
Switch-Ebene	L2/L3	Unterstützte Sicherheitsalgorithmen	HTTPS, SHA-2, SSL/TLS
Quality of Service (QoS) Support	✓	SSH-/SSL-Unterstützung	✓
Web-basiertes Management	✓	Loop Protection	✓
ARP-Inspektion	✓	Multicast-Funktionen	
Konfiguration der Standorteinstellungen (CLI)	✓	Multicast Unterstützung	✓
MIB Unterstützung	✓	Design	
Anschlüsse und Schnittstellen		Rack-Einbau *	✓
Menge Modul-Steckplätze SFP+	10	Produktfarbe	Schwarz
Netzstecker	AC-Eingangsbuchse	LED-Anzeigen	✓
Netzwerk		Leistungen	
Netzstandard *	IEEE 802.1p, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3z	RAM-Speicher	256 MB
10G-Unterstützung *	✓	Flash-Speicher	32 MB
Port-Spiegelung	✓	Leistung	
Unterstützung Datenflusssteuerung	✓	Energiequelle *	AC
Link Aggregation	✓	AC Eingangsspannung	100 - 240 V
Broadcast-Sturmkontrolle	✓	AC Eingangsfrequenz	50 - 60 Hz
Spannbaum-Protokoll	✓	Stromverbrauch (max.)	24,9 W
Ethernet LAN Datentransferraten	1000,2500,5000,10000 Mbit/s	Power over Ethernet (PoE)	
VLAN-Unterstützung	✓	Power over Ethernet (PoE) *	✗
Anzahl der VLANs	4000	Betriebsbedingungen	
Datenübertragung		Betriebstemperatur	-20 - 50 °C
Routing-/Switching-Kapazität *	240 Gbit/s	Temperaturbereich bei Lagerung	-40 - 70 °C
Transferrate	178,5 Mpps	Relative Luftfeuchtigkeit in Betrieb	5 - 95%
MAC-Adressentabelle *	16000 Eintragungen	Luftfeuchtigkeit bei Lagerung	5 - 95%
Statische Route	✓	Wärmeableitung	84,91 BTU/h
Jumbo Frames Unterstützung	✓	Gewicht und Abmessungen	
Jumbo-Frames	12000	Breite	484 mm
Datenpaket-Pufferspeicher	2 MB	Tiefe	337 mm
Sicherheit		Höhe	79 mm
DHCP-Funktionen	DHCP client, DHCP relay	Gewicht	3,63 kg
Zugriffskontrollliste	✓	Logistikdaten	
		Warentarifnummer (HS)	85176990



4718937620791

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-MAY-2023. Prints or copies of Information are only valid on the printed Publication date