

ZYXEL

Zyxel XGS2220-54 Managed L3 Gigabit Ethernet (10/100/1000)

Marke : Zyxel

Artikel-Code: XGS2220-54-EU0101F

Produktname : XGS2220-54

Zyxel XGS2220-54. Switch-Typ: Managed, Switch-Ebene: L3. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 48, Anzahl installierte SFP Module: 4. MAC-Adressentabelle: 32000 Eintragungen, Routing-/Switching-Kapazität: 216 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack-Einbau



Management-Funktionen		Multicast-Funktionen	
Switch-Typ *	Managed	Multicast Listener Discovery (MLD) Snooping	MLD v1/v2
Switch-Ebene	L3		
Quality of Service (QoS) Support	✓		
ARP-Inspektion	✓		
Anschlüsse und Schnittstellen		Protokolle	
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	48	GARP VLAN Registration Protocol (GVRP)	✓
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)		
Anzahl 10G Ethernet (Kupfer)-Ports	2		
Anzahl installierte SFP Module *	4		
Netzwerk		Design	
Netzstandard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z	Rack-Einbau *	✓
10G-Unterstützung *	✓		
Routing Eingänge	64		
Datenübertragung		Leistungen	
Routing-/Switching-Kapazität *	216 Gbit/s	Speicherkapazität	1024 MB
Transferrate	161 Mpps	Flash-Speicher	64 MB
MAC-Adressentabelle *	32000 Eintragungen	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	298,735 h
Jumbo Frames Unterstützung	✓		
Datenpaket-Pufferspeicher	2 MB		
Sicherheit		Leistung	
DHCP-Funktionen	DHCP relay, DHCP server	Energiequelle *	AC
IGMP snooping	✓	Netzteil enthalten *	✓
IGMP-Proxy	✓	AC Eingangsspannung	100 - 240 V
Unterstützte Sicherheitsalgorithmen	SNMP, SNMPv2, SNMPv3	AC Eingangsfrequenz	50 - 60 Hz
Autentifizierungstyp	IEEE 802.1x, RADIUS, TACACS+	Stromverbrauch (max.)	57,31 W
		Power over Ethernet (PoE)	
		Power over Ethernet (PoE) *	✗
		Betriebsbedingungen	
		Betriebstemperatur	-20 - 50 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C
		Relative Luftfeuchtigkeit in Betrieb	10 - 95%
		Luftfeuchtigkeit bei Lagerung	10 - 90%
		Wärmeableitung	195,43 BTU/h
		Gewicht und Abmessungen	
		Breite	441 mm
		Tiefe	270 mm
		Höhe	44 mm

Gewicht und Abmessungen

Gewicht	3,85 kg
---------	---------



4718937625093

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-AUG-2023. Prints or copies of Information are only valid on the printed Publication date